



JMS SOUTHEAST INCORPORATED CERTIFIES THIS DRAWING IS IN ACCORDANCE WITH JMS SOUTHEAST INCORPORATED ENGINEERING SPECIFICATIONS AND ACCURATELY REPRESENTS THE EQUIPMENT FURNISHED. THIS DRAWING IS THE SOLE PROPERTY OF JMS SE, AND MUST BE RETURNED UPON DEMAND IT MAY NOT BE REPRODUCED NOR THE INFORMATION CONTAINED THEREIN USED WITHOUT THE WRITTEN PERMISSION OF JMS SOUTHEAST INCORPORATED

Company Name:
ENVIROSEP

Reference Data:

Drawing #:

QD9215

Rev 0

Project Name:

TOLERANCE TABLE:
PROBE(L): 0-48" ±18"
48"-144" ±14"
144"- ±1" / ±2"
WIRE(L): >24" ±12" / ±1"
>24" ±12" / ±2"
PROT. TUBE (P8U): ±14"
FRACTIONAL DIM: ±1/8"
DECIMAL DIM: ±1/8"
XX ± 0.10"
XXX ± 0.010"
XXXX ± 0.005"
UNLESS STATED OTHERWISE

Generated By

Date

Initials

02/13/26



JMS SOUTHEAST, INC.
Temperature Measurement
105 Temperature Lane
Statesville, North Carolina 28677
Phone: (704) 873-1835
Fax: (704) 878-6166
www.jms-se.com
Email: sensors@jms-se.com

Not to Scale

Rev. 10-01-2015

Sensor	
Sensor	RTD, 100 Ω, α=0.0385, ±0.15°C Accuracy at 0°C, 3 Wire, Dual Element, Max Temp: < 200°C (392°F)
Construction	Standard Costr., Insul. Teflon, 316 SS, 1/4" OD, 2-1/2" L, Normal, Closed Tip
Attaching Device	Double Threaded SS Spring-Loaded Fitting w/ Bayonet-Union-Nipple: 1/2" NPTM; N Len: 3-1/2"; 304 SS; 150 psi - A351 Spec
Cold-End	Head: Explosion Proof, Cast Iron, Screw Cap, NEMA 4, 3/4" x 3/4" Conduit Conn.
Tagging	Stainless Steel Tag
JMS Part #	3EDBNK2.5"BB{UN3.5"H1}PZZYZSI