


| Sensor | | Project Name: | Generated By | JMS SOUTHEAST, INC. |
|-------------------------|---|---|---------------------------------------|---|
| Sensor | Type K Thermocouple, Single Element, Standard Limits [ASTM E230-11], Max Temp: > 660°C (1220°F) | TOLERANCE TABLE: PROBE(L): 0" - 48" ±18" 48" - 144" ±14" 144" + 24" - 1" / +2" WIRE(L): <24" - 12" / +1" >24" - 12" / +2" PROT. TUBE (P8U): ±14" FRACTIONAL DIM: ±1/8" DECIMAL DIM: ±1.6" | Date: 02/16/26 Initials: Not To Scale | Temperature Measurement 105 Temperature Lane Statesville, North Carolina 28677 Phone: (704) 873-1835 Fax: (704) 878-6166 www.jms-se.com Email: sensors@jms-se.com |
| Construction | Stabaloy, MgO Swaged, 1/4" OD, 27-1/2" L, Ungrounded | Generated By | |  |
| Attaching Device | Double Threaded SS Spring-Loaded Fitting, 1/2" NPTM | Date: 02/16/26 | Initials: Not To Scale | |
| Cold-End | Head: Explosion Proof, Aluminum, Screw Cap & Chain, NEMA 4X, 1/2" x 3/4" Conduit Conn. | | | |
| JMS Part # | 1K1BVU27.5"SPZZI | | | Rev. 10-01-2015 |