



Suitable for Sanitary applications  
Excellent corrosion resistance  
Weather tight seal  
Rain and dust resistant  
Very lightweight  
NEMA 4X  
Continuous use temp rating of 198°F. (PP)



HOLE PATTERNS FOR MOUNTING  
TERMINAL BLOCK/ TRANSMITTER



**JMS PART #**  
**6WP**

JMS SOUTHEAST INCORPORATED CERTIFIES THIS DRAWING IS IN ACCORDANCE WITH JMS SOUTHEAST INCORPORATED ENGINEERING SPECIFICATIONS AND ACCURATELY REPRESENTS THE EQUIPMENT FURNISHED. THIS DRAWING IS THE SOLE PROPERTY OF JMS SE, AND MUST BE RETURNED UPON DEMAND IT MAY NOT BE REPRODUCED NOR THE INFORMATION CONTAINED THEREIN USED WITHOUT THE WRITTEN PERMISSION OF JMS SOUTHEAST INCORPORATED

Company Name:

**JMS-SE HEADS**

**COLD END TERMINATION  
SELECTION = WP**

Drawing #:  
**18262-M**

TOLERANCE TABLE:

PROBE (L): 0-48" ±1/8"  
48"-144" ±1/4"  
144"+ -1" / +2"  
WIRE (L): <24" -1/2" / +1"  
>24" -1/2" / +2"  
PROT. TUBE (P&U): ±1/4"  
FRACTIONAL DIM: ±1/8"  
DECIMAL DIM:  
X.X ± 0.10"  
X.XX ± 0.010"  
X.XXX ± 0.005"  
UNLESS STATED OTHERWISE

Approvals


Initials

Date

Drafting

Engineering

Second



**JMS SOUTHEAST, INC.**  
Temperature Measurement  
105 Temperature Lane  
Statesville, North Carolina 28677  
Phone: (704) 873-1835  
Fax: (704) 878-6166  
www.jms-se.com  
Email: sensors@jms-se.com

REV. 4-10-2009

#	DESCRIPTION
1	HEAD, FDA APPROVED WHITE PLASTIC, SCREW CAP & CHAIN, 1/2" X 3/4" FNPT