

## ANSI: TYPE, J - Iron / Constantan

Catalog Number	Gauge Size	Conductors	*Ohms	Primary Insulation	Outer Jacket	Min.-Max. O.D.	Est. Shpg. Wt. per M
PP161JX	16	Solid	.137	Polyvinyl Chloride	Polyvinyl Chloride	.111 x .188"	27 lbs.
PA161JX	16	Solid	.137	PVC/Alum. Mylar Shield (Twisted)	PVC	.222"	28 lbs.
PA201JX	20	Solid	.357	PVC/Alum. Mylar Shield (Twisted)	PVC	.184"	20 lbs.
PP201JX	20	Solid	.357	Polyvinyl Chloride	Polyvinyl Chloride	.095 x .158"	14 lbs.
PP202JX	20	Stranded	.317	Polyvinyl Chloride	Polyvinyl Chloride	.115 x .190"	14 lbs.
PX201JX	20	Solid	.357	(FEP) Extruded Teflon	Extruded Teflon	.072 x .124"	11 lbs.

## ANSI: TYPE, K - Chromel / Alumel

PA161KX	16	Solid	.233	PVC/Alum. Mylar Shield (Twisted)	PVC	.222"	28 lbs.
PP161KX	16	Solid	.233	Polyvinyl Chloride	Polyvinyl Chloride	.116 x .188"	27 lbs.
PA201KX	20	Solid	.590	PVC/Alum. Mylar Shield (Twisted)	PVC	.184"	20 lbs.
PP201KX	20	Solid	.590	Polyvinyl Chloride	Polyvinyl Chloride	.195 x .158"	14 lbs.
PP202KX	20	Stranded	.538	Polyvinyl Chloride	Polyvinyl Chloride	.115 x .190"	14 lbs.

## ANSI: TYPE, T - Copper / Constantan

PP141TX	14	Solid	.074	Polyvinyl Chloride	Polyvinyl Chloride	.130 x .226"	37 lbs.
PA161TX	16	Solid	.118	PVC/Alum. Mylar Shield (Twisted)	PVC	.222"	20 lbs.
PP161TX	16	Solid	.118	Polyvinyl Chloride	Polyvinyl Chloride	.111 x .188"	28 lbs.
PA201TX	20	Solid	.298	PVC/Alum. Mylar Shield	PVC	.184"	20 lbs.
PP201TX	20	Solid	.298	Polyvinyl Chloride	Polyvinyl Chloride	.095 x .158"	15 lbs.

## ANSI: TYPE, E - Chromel / Constantan

PA161EX	16	Solid	.278	PVC/Alum. Mylar Shield (Twisted)	PVC	.222"	20 lbs.
PP201EX	20	Solid	.704	Polyvinyl Chloride	Polyvinyl Chloride	.095 x .158"	15 lbs.

## ANSI: TYPE, S and R - Platinum / Rhodium

PP161SX	16	Solid	.016	Polyvinyl Chloride	Polyvinyl Chloride	.116 x .250"	27 lbs.
GG201SX	20	Solid	.040	Glass Braid	Glass Braid	.059 x .105"	8 lbs.
PP201SX	20	Solid	.040	Polyvinyl Chloride	Polyvinyl Chloride	.095 x .158"	14 lbs.

\*ohms per double foot at 20°C (68°F).